



## FEATURES

- Door is easily removed and can be installed to open in any direction with our innovative spring hinge system
- AP installs using the included ceiling tile grid clip shipped with the AP onto an integrated mounting plate with no tools
- Key lock for security
- Includes integrated tabs for securing enclosure mount to permanent building structure
- Shallow back box (1.5") allows installation into the tightest ceiling clearances




## BENEFITS

- Easy to Install
- No ceiling tile grid modification necessary (if mounting into a 2'x2' grid)
- Service the AP without removing the enclosure mount from ceiling
- Lightweight aluminum design reduces ceiling strain and load
- Simple, one person installation
- Blends seamlessly into ceiling
- No tools required for installation



## MOUNT SHIPS WITH

- 2x2 Suspended Ceiling Tile Enclosure Mount with installed Aruba 2 Door
- Cord Grip
- Key



Integrated Mounting Plate




Key Lock



Integrated Mounting Plate Shown with AP  
Supplied Ceiling Tile Clip



Integrated mounting tabs on two sides



Spring Hinge



# ARUBA AP SUSPENDED CEILING TILE ENCLOSURE MOUNT (330/340 STYLE) ATS-CT-ARUBA2-2X2



## MECHANICAL SPECIFICATIONS

---

Dimensions: 23.75" x 23.75" x 1.5" (603.25mm x 603.25mm x 38.1mm)

Weight (without AP): 3.75 lb (1.70 kg)

Material: Aluminum. Steel (Key Lock & Latch)

Color: White

Lock: Key Lock

Installation: Suspended Ceiling (includes tabs for securing to building structure)

Equipment Installation: Integrated Mounting Plate Using supplied Ceiling Tile Grid Clip that ships with the AP

Load Capacity: 5.5. lbs. (2.5 kg.)



## ENVIRONMENTAL SPECIFICATIONS

---

Installation Environment: Indoor



## STANDARDS, TESTING AND CERTIFICATIONS

---

Designed to meet NEC300-22 and 300-23 to mount the Aruba APs in plenum/air handling areas

UL2416: Investigation of the enclosure system covers the enclosure only.



## WARRANTY

---

2 Year Limited Warranty