



LTE 2 ELEMENT INDOOR/OUTDOOR OMNI ANTENNA WITH SMA



The AccelTex Solutions LTE antenna is a perfect compliment to any LTE radio. This small form factor antenna comes with an integrated threaded bolt mount and is suitable for a broad range of outdoor applications.

Part Number: ATS-OO-LTE-2-2SP-144



ELECTRICAL SPECIFICATIONS

LTE Antenna (Main)

Frequency Range: 698-960/1710-2690 MHz
Gain: 2.5 dBi
Polarization: Linear

VSWR: ≤ 3.0
Impedance: 50 Ω

LTE Antenna (AUX)

Frequency Range: 698-960/1710-2690 MHz
Gain: 2 dBi
Polarization: Linear

VSWR: ≤ 3.0
Impedance: 50 Ω



MECHANICAL SPECIFICATIONS

Dimensions: 3.2" Dia x 0.57" H (81.3mm Dia x 14.6mm H)
Weight: 0.55 lb (0.25 kg)
Installation: Threaded Bolt with Nut
Cable Type: RG174

Radome Material: ABS
Connector: SMA
Number of Leads: 2
Cable Length: 12' (3,657.6mm)



ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Outdoor
Operating Temperature: -40 to 185°F (-40 to 85°C)
IP Rating: IP66

WARRANTY

2 Year Limited Warranty