



2.4/5 GHZ 8/10 DBI 6 ELEMENT INDOOR/OUTDOOR PATCH ANTENNA WITH RPTNC ATS-OP-245-810-6RPTP-36-V2



ELECTRICAL SPECIFICATIONS

Frequency Range: 2.4-2.5/4.9-5.85 GHz
Gain: 8/10 dBi
Polarization: Vertical
Horizontal Beamwidth: 55°/45°
Vertical Beamwidth: 65°/45°

VSWR: < 2.0:1
Impedance: 50 Ω
Isolation: > 20 dB
Lightning Protection: DC Grounded
Max Input Power: 100 W



MECHANICAL SPECIFICATIONS

Dimensions: 8.1" H x 7" W x 1.8" D (207x177x46mm)
Weight: 1.2 lb (0.5 kg)
Installation: Threaded bolt w/ nut and articulating wall/pole mount (included)
Installation Hole Diameter: 1" (25mm)
Pole Diameter: 2" (50mm)

Radome Material: ASA
Connector: RPTNC Plug
Number of Leads: 6
Cable Length: 36"
Cable Type: ATS-195




ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Indoor/Outdoor
Operating Temperature: -40 to 149°F (-40 to 65°C)
Wind Velocity: 130 mph (210 km/h)
IP Rating: IP66



HORIZONTAL



VERTICAL

