



ELECTRICAL SPECIFICATIONS

Frequency Range: 2.4-2.48/5.15-5.85/6-7.125 GHz
 Gain: 4/7/7 dBi
 Polarization: 4 Vertical / 4 Horizontal
 Horizontal Beamwidth: 75°/50°/45°
 Vertical Beamwidth: 75°/50°/45°

VSWR: $\leq 1.5:1$, max 2.0
 Isolation: >30 dB
 Impedance: 50 Ω
 Lightning Protection: None
 Max Input Power: 50 W per port



MECHANICAL SPECIFICATIONS

Dimensions: 11.81" x 11.81" x 1.9"
 (300x300x48mm)
 Weight: 1.5 lb (0.68 kg)
 Installation: Flush Mount to Wall or included
 Articulating mount

Radome Material: ABS
 Connector: Straight DART-8
 Number of Leads: 1 (8 ports on DART Assembly)
 Cable Length: 36" (910mm)
 Cable Type: LMR-100



ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Indoor/Outdoor
 Operating Temperature: -40 to 158°F (-40 to 70°C)
 Wind Velocity: 134 mph (216 km/h)
 IP Rating: IP66

WARRANTY

2 Year Limited Warranty



HORIZONTAL

VERTICAL

