



# 110 AMP HOUR 20X16X10 SOLAR SOLUTION WITH 90 W SOLAR PANEL AND POE OUTPUT



The AccelTex Solutions Solar Solutions are a complete remote power solution designed for off-grid operation to power various electronics. These solar solutions are fully configured and provide multiple output power options, such as PoE and DC power.

Part Number: ATS-SOLR-110AH-90W-201610PCS-POE



## FEATURES

- Fully integrated unit includes charge controller, battery, enclosure and solar panel
- (1) Output for 802.3af or 802.3at and (1) Output for 12V DC (10 Amps)
- Batteries are charged via the solar panel
- Charge controller protects against over-charging and over discharging of the batteries
- Enclosure and Solar Panel ship with wall and pole mounts
- Outdoor-Rated



## BENEFITS

- Self-Contained Unit for easy install
- Provides isolated and uninterrupted power
- Space for mounting electronics



## ADDITIONAL COMPATIBLE ACCESSORY ITEMS

- 50W PoE Injector (ATS-50W-POE-INJ)
- 60W PoE Injector (ATS-60W-POE-INJ)
- PoE Switch (ATS-POES-12VDC-56VDC)



## APPLICATIONS

- Security Cameras
- Outdoor Wi-Fi
- Parking Lots and Garages
- Cellular Backhaul
- Remote Monitoring and Control
- Remote Sites
- Temporary Locations
- Disaster Relief

# 110 AMP HOUR 20X16X10 SOLAR SOLUTION WITH 90 W SOLAR PANEL AND POE OUTPUT

Part Number: ATS-SOLR-110AH-90W-181610PCS-POE



## MECHANICAL SPECIFICATIONS

Enclosure Dimensions: 20" H x 16" W x 10" D (508 mm H x 406.4 mm W x 254 mm D)  
Enclosure Color: White  
Enclosure Material: Powder Coated Steel  
Enclosure Door Type: Solid  
Enclosure Lock Type: Padlockable Turn Latch  
Enclosure Installation: Wall/Pole Mount  
Enclosure Pole Mount Diameter: Up to 12" Diameter Pole (304.8 mm)  
Solar Panel Dimensions: 46.25" L x 21.06" H x 1.37" D (1,175 mm L x 535 mm H x 35 mm D)  
Solar Panel Installation: Wall/Pole Mount  
Solar Panel Pole Mount Diameter: Up to 12" Diameter Pole (304.8 mm)



## ELECTRICAL SPECIFICATIONS

System Output Power Options: (1) Output for 802.3af or 802.3at and (1) Output for 12V DC (Supports up to 10 Amps)  
Solar Panel Input: 90W  
Solar Panel Rated Current: 5.11 Amps  
Charge Controller Max Input: 10 Amps



## ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Outdoor  
Operating Temperature: -4 to 122°F (-20 to 50°C)



## SYSTEM COMPONENTS

- (1) 12V 110Ah AGM Sealed Lead Acid Battery
- 20x16x10 White Powder Coated Steel Enclosure with Solid Door, Padlockable Turn Latch and Wall/Pole Mount
- 90 W Monocrystalline Solar Panel with Wall/Pole Mount
- Charge Controller (1 Output for 802.3af or 802.3at and 1 Output for 12V DC, 10 Amps)
- Battery Wiring Harnesses and Terminal Blocks
- Battery Tray
- Battery J Hook
- Battery Gel
- (3) 20 Amp Breakers
- (1) 10' Dual Conductor MC4 Solar Cable
- (1) PG16 Oval Cord Grip for Solar Cable
- (1) PG16 Cord Grip for Ethernet